

Rys. K-17 Schody w osiach "D-F"/"3-5"

WYKAZ STALI ZBROJENIOWEJ

Nr	Ø	#	L	n	A-0(St0S)	AIIIIN (RB 500 W)		
			[m]	[szt.]	6	8	10	12
1		12	1,35	14				18,90
2		8	1,72	8		13,76		
3		12	1,28	14				17,92
4		12	1,00	14				14,00
5		12	4,12	14				57,68
6		12	2,35	14				32,90
7		12	1,39	84				116,76
8		8	1,35	130		175,50		
9		8	3,25	89		289,25		
10		12	7,10	14				99,40
11		12	1,61	42				67,62
12		12	2,60	42				109,20
13		12	3,06	42				128,52
14		12	6,91	28				193,48
15		12	1,86	28				52,08
16		12	2,95	14				41,30
17		12	2,81	28				78,68
18		12	6,97	28				195,16
19		12	2,85	14				39,90
20		12	3,25	8				26,00
21		12	1,95	11				21,45
22		12	0,92	6				5,52
23		12	3,50	1				3,50
24		12	231,00	1				231,00
25	6		1,10	70	77,00			
26	6		0,90	130	117,00			
Długość całkowita [m]					194,00	478,51		1550,97
Masa 1 mb [kg/m]					0,222	0,395		0,888
Masa całkowita [kg]					43,07	189,01		1377,26
Razem [kg]					1609			