










KD-6

Poziom porównawczy 135,00 m n.p.m

Rzędna terenu projektowanego		142,22	143,48		142,43	143,83		145,23		145,12	146,52		147,94
Rzędna dna kanału		142,22	142,23	143,45		142,43	143,83		145,23		145,12	146,52	147,94
Zagłębienie dna kanału [m]		1,26	1,22	1,19		1,40	1,30		1,40		1,40	1,40	1,40
Odległości [m]		3,00	38,30				53,50				26,00		26,30
Średnice, materiał		PPØ315				PPØ250				PPØ250		PPØ250	
Spadek		5,0 ‰				28,0 ‰				45,8 ‰		54,0 ‰	
Długość trasy [m]		0,00	3,00		41,30		94,80		120,80		147,10		



KD-5

poziom porównawczy 135,00 m n.p.m.

zróżnicowanie terenu projektowanego		142,25	143,48		
zróżnicowanie dna kanału		142,27	143,50		
głębokość dna kanału [m]	1,23	1,23	1,30	1,42,41	143,86
długości [m]	4,80	34,10	38,50		
średnice, materiał	PPØ250				
spadek	Spadek				4,0 ‰
długość trasy [m]	0,00	4,80	38,90		77,40
	D33		D31		D30

